

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## BASE COAT SPARKLING GLASS

Version 1.17

Revision Date 27.01.2016

Print Date 04.05.2016

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : BASE COAT SPARKLING GLASS  
Product code : L0660009

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Paints, varnishes and enamels  
Chemical nature : Mono compound enamel - finish coat

#### 1.3 Details of the supplier of the safety data sheet

Company : Lechler SpA  
Via Cecilio 17  
22100 Como- CO-  
Telephone : +39031586111  
Telefax : +39031586206  
E-mail address : safety@lechler.eu  
Responsible/issuing person

Imported by:  
Smits Group  
59-65 Greenmount Drive  
East Tamaki, Auckland  
ph +6492746871  
fax +6492740991

NZ Poisons Centre 03 4747000 or 0800 764766  
Available 24 Hours

#### 1.4 Emergency telephone number

Tel. +39-031-586301 Fax +39-031-586299  
This telephone number is available during office hours only. (8.00-18.00)

### SECTION 2: Hazards identification

HSNO Classification: 3.1B, 6.3A, 8.3A, 6.9B

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2	H225: Highly flammable liquid and vapour.
Skin irritation, Category 2	H315: Causes skin irritation.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Specific target organ toxicity - single exposure, Category 3	H336: May cause drowsiness or dizziness.
Specific target organ toxicity - single exposure, Category 3	H335: May cause respiratory irritation.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## BASE COAT SPARKLING GLASS

Version 1.17

Revision Date 27.01.2016

Print Date 04.05.2016

Signal word	:	Danger	
Hazard statements	:	H225 H315 H318 H335 H336	Highly flammable liquid and vapour. Causes skin irritation. Causes serious eye damage. May cause respiratory irritation. May cause drowsiness or dizziness.
Precautionary statements	:	<b>Prevention:</b> P210  P233 P261 <b>Response:</b> P305 + P351 + P338 + P310  P362 + P364  P370 + P378	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Avoid breathing vapours. <b>IF IN EYES:</b> Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician. Take off contaminated clothing and wash it before reuse. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

- 78-83-1 2-methylpropan-1-ol

### 2.3 Other hazards

None known.

No hazards resulting from the material as supplied.

The information required is contained in this Material Safety Data Sheet.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical nature : Liquid pigmented dispersion

#### Hazardous components

Chemical Name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration [%]
xylene	1330-20-7 215-535-7 01-2119488216-32	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315	>= 30 - < 50
2-methylpropan-1-ol	78-83-1 201-148-0	Flam. Liq. 3; H226 STOT SE 3; H335, H336	>= 20 - < 25

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## BASE COAT SPARKLING GLASS

Version 1.17

Revision Date 27.01.2016

Print Date 04.05.2016

	01-2119484609-23	Skin Irrit. 2; H315 Eye Dam. 1; H318	
4-hydroxy-4-methylpentan-2-one	123-42-2 204-626-7 01-2119473975-21	Flam. Liq. 3; H226 Eye Irrit. 2; H319 STOT SE 3; H335	>= 15 - < 17,5
cyclohexanone	108-94-1 203-631-1 01-2119453616-35	Flam. Liq. 3; H226 Acute Tox. 4; H332	>= 15 - < 17,5
ethyl acetate	141-78-6 205-500-4 01-2119475103-46	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 EUH066	>= 1 - < 5
butan-2-ol	78-92-2 201-158-5 01-2119475146-36	Flam. Liq. 3; H226 Eye Irrit. 2; H319 STOT SE 3; H336 STOT SE 3; H335	>= 1 - < 5
Low boiling point naphtha - unspecified	64742-95-6 265-199-0 01-2119455851-35-0006	Flam. Liq. 3; H226 STOT SE 3; H335, H336 Aquatic Chronic 2; H411 Asp. Tox. 1; H304 EUH066	>= 0,1 - < 1
1,2,4-trimethylbenzene	95-63-6 202-436-9	Flam. Liq. 3; H226 Acute Tox. 4; H332 Eye Irrit. 2; H319 STOT SE 3; H335 Skin Irrit. 2; H315 Aquatic Chronic 2; H411	>= 0,1 - < 1
1,3,5-trimethylbenzene	108-67-8 203-604-4	Flam. Liq. 3; H226 STOT SE 3; H335 Aquatic Chronic 2; H411	>= 0,1 - < 1

For the full text of the H-Statements mentioned in this Section, see Section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- General advice : When symptoms persist or in all cases of doubt seek medical advice.  
Never give anything by mouth to an unconscious person.
- If inhaled : Remove to fresh air.  
Keep patient warm and at rest.  
If breathing is irregular or stopped, administer artificial respiration.  
If unconscious place in recovery position and seek medical advice.

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## BASE COAT SPARKLING GLASS

Version 1.17

Revision Date 27.01.2016

Print Date 04.05.2016

- 
- |                         |   |
|-------------------------|---|
| In case of skin contact | : Take off all contaminated clothing immediately.<br>Wash skin thoroughly with soap and water or use recognized skin cleanser.<br>Do NOT use solvents or thinners.<br>Put shower on working place |
| In case of eye contact  | : Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.<br>Seek medical advice.<br>Put eye-washer on working place<br>Remove contact lenses.             |
| If swallowed            | : If accidentally swallowed obtain immediate medical attention.<br>Do NOT induce vomiting.<br>Keep at rest.   |

### 4.2 Most important symptoms and effects, both acute and delayed

- |          |                             |
|----------|-----------------------------|
| Symptoms | : No information available. |
| Risks    | : No information available. |

### 4.3 Indication of any immediate medical attention and special treatment needed

- |           |  |
|-----------|--|
| Treatment | : The first aid procedure should be established in consultation with the doctor responsible for industrial medicine.<br>Seek medical advice. |
|-----------|--|

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- |                                |   |
|--------------------------------|---|
| Suitable extinguishing media   | : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.<br>Keep containers and surroundings cool with water spray. |
| Unsuitable extinguishing media | : Do NOT use water jet.   |

### 5.2 Special hazards arising from the substance or mixture

- |                                      |   |
|--------------------------------------|---|
| Specific hazards during firefighting | : As the product contains combustible organic components, fire will produce dense black smoke containing hazardous products of combustion (see section 10).<br>Exposure to decomposition products may be a hazard to health.<br>Cool closed containers exposed to fire with water spray.<br>Collect contaminated fire extinguishing water separately. This must not be discharged into drains.<br>Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. |
|--------------------------------------|---|

### 5.3 Advice for firefighters

- |   |  |
|---|--|
| Special protective equipment for firefighters | : Wear self-contained breathing apparatus for firefighting if necessary. |
|---|--|

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## BASE COAT SPARKLING GLASS

Version 1.17

Revision Date 27.01.2016

Print Date 04.05.2016

---

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Solvent vapours are heavier than air and may spread along floors.  
Ensure adequate ventilation.  
Use personal protective equipment.  
Evacuate personnel to safe areas.  
Keep people away from and upwind of spill/leak.  
Ventilate the area.

#### 6.2 Environmental precautions

Environmental precautions : Try to prevent the material from entering drains or water courses.  
If the product contaminates rivers and lakes or drains inform respective authorities.

#### 6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Clean with detergents. Avoid solvents.  
Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).  
Pick up and transfer to properly labelled containers.  
Clean contaminated surface thoroughly.  
Dam up.  
Soak up with inert absorbent material and dispose of as hazardous waste.

#### 6.4 Reference to other sections

Refer to section 15 for specific national regulation.

---

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding of the given occupational exposure limits (see section 8).  
Use only in area provided with appropriate exhaust ventilation.  
Avoid contact with skin, eyes and clothing.  
Smoking, eating and drinking should be prohibited in the application area.  
Avoid inhalation of vapour or mist.  
For personal protection see section 8.  
Thoroughly mix before using  
After using, store in a well-sealed container

Advice on protection against fire and explosion : Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## BASE COAT SPARKLING GLASS

Version 1.17

Revision Date 27.01.2016

Print Date 04.05.2016

the occupational exposure limits.  
When transferring from one container to another apply earthing measures and use conductive hose material.  
No sparking tools should be used.  
The product should only be used in areas from which all naked lights and other sources of ignition have been excluded.  
No smoking.

### 7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Observe label precautions.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Solvent vapours are heavier than air and may spread along floors.  
Vapours may form explosive mixtures with air.  
Electrical installations / working materials must comply with the technological safety standards.  
Keep away from sources of ignition - No smoking.  
Store between 5° an 35°C in a dry, well ventilated place away from source of heat, ignition and direct sunlight.  
Store in accordance with the particular national regulations.
- Advice on common storage : Keep away from oxidising agents and strongly acid or alkaline materials.

### 7.3 Specific end use(s)

- : This information is not available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Components	CAS-No.	Value	Control parameters	Update	Basis
xylenes	1330-20-7	TWA	50 ppm 221 mg/m <sup>3</sup>	2000-06-16	2000/39/EC
Further information	:	skin: Identifies the possibility of significant uptake through the skinIndicative			
		STEL	100 ppm 442 mg/m <sup>3</sup>	2000-06-16	2000/39/EC
Further information	:	skin: Identifies the possibility of significant uptake through the skinIndicative			
2-methylpropan-1-ol	78-83-1	TWA	50 ppm		ACGIH
4-hydroxy-4-methylpentan-2-one (Technical)	123-42-2	TWA	50 ppm		ACGIH
cyclohexanone	108-94-1	TWA	10 ppm	2000-06-16	2000/39/EC

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## BASE COAT SPARKLING GLASS

Version 1.17

Revision Date 27.01.2016

Print Date 04.05.2016

(Vapour and gas)			40,8 mg/m <sup>3</sup>		
Further information	:	skin: Identifies the possibility of significant uptake through the skinIndicative			
		STEL	20 ppm 81,6 mg/m <sup>3</sup>	2000-06-16	2000/39/EC
Further information	:	skin: Identifies the possibility of significant uptake through the skinIndicative			
ethyl acetate	141-78-6	TWA	400 ppm		ACGIH
butan-2-ol	78-92-2	TWA	100 ppm		ACGIH
1,2,4-trimethylbenzene	95-63-6	TWA	20 ppm 100 mg/m <sup>3</sup>	2000-06-16	2000/39/EC
Further information	:	Indicative			
mesitylene	108-67-8	TWA	20 ppm 100 mg/m <sup>3</sup>	2000-06-16	2000/39/EC
Further information	:	Indicative			

## 8.2 Exposure controls

### Personal protective equipment

- Respiratory protection : Apply technical measures to comply with the occupational exposure limits.  
This should be achieved by a good general extraction and -if practically feasible- by the use of a local exhaust ventilation.  
If the occupational exposure limits cannot be met, in exceptional cases suitable respiratory equipment should be worn only for a short period of time.  
Respirator with combination filter for vapour/particulate (EN 141).
- Hand protection : Solvent-resistant gloves (butyl-rubber)  
For prolonged or repeated contact use protective gloves.  
Protective gloves complying with EN 374.  
Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves.  
Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.  
If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves.  
Barrier creams may help to protect the exposed areas of skin, they should however not be applied once exposure has occurred.  
Skin should be washed after contact.  
Wash your hands and put on barrier creams
- Eye protection : Chemical resistant goggles must be worn.
- Skin and body protection : Skin should be washed after contact.  
Working clothes must not consist of textiles, which show a dangerous melting behaviour in case of fire.  
Personnel should wear protective clothing.  
Workers should wear antistatic footwear.

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## BASE COAT SPARKLING GLASS

Version 1.17

Revision Date 27.01.2016

Print Date 04.05.2016

### Environmental exposure controls

General advice : Try to prevent the material from entering drains or water courses.  
If the product contaminates rivers and lakes or drains inform respective authorities.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Appearance	: liquid
Odour	: solvent-like
Flash point	: 0 - < 21 °C
Ignition temperature	: not determined
Lower explosion limit	: No data available
Upper explosion limit	: No data available
Auto-ignition temperature	: not applicable
pH	: not determined
Freezing point	: not applicable
Boiling point	: not determined
Vapour pressure	: 1,000 hPa at 50 °C
Density	: 0,8855 g/cm <sup>3</sup>
Water solubility	: not determined
Partition coefficient: n-octanol/water	: No data available
Solubility in other solvents	: not determined
Flow time	: 15 s 3 mm Method: ASTM D 1200 '82
Relative vapour density	: not applicable
Evaporation rate	: not determined

### 9.2 Other information

Solids by weight	: 3,53 %
Volatile organic compounds (VOC) content	: 96,46 %



# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## BASE COAT SPARKLING GLASS

Version 1.17

Revision Date 27.01.2016

Print Date 04.05.2016

---

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

None reasonably foreseeable.

#### 10.2 Chemical stability

The product is chemically stable.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

#### 10.4 Conditions to avoid

Conditions to avoid : Our products were manufactured in compliance with safety standards to avoid decomposition and degrading under the defined conditions.  
Taking the product type into account, it is advisable to leave the product in its original packaging thus avoiding transferring it.

#### 10.5 Incompatible materials

Materials to avoid : Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

#### 10.6 Hazardous decomposition products

Hazardous decomposition products : Carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO), oxides of nitrogen (NO<sub>x</sub>), dense black smoke.

Thermal decomposition : not applicable

---

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

##### Product

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l, 4 h, vapour, Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg, Calculation method

Skin corrosion/irritation : Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in desiccation of the skin., The product may be absorbed through the skin.

Serious eye damage/eye irritation : The liquid splashed in the eyes may cause irritation and reversible damage.

Further information : The concentration of each substance should be borne in mind in assessing the toxicological effects deriving from the preparation.

##### Components:

xylene :

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## BASE COAT SPARKLING GLASS

Version 1.17

Revision Date 27.01.2016

Print Date 04.05.2016

Acute dermal toxicity : Acute toxicity estimate: 1.100 mg/kg, Converted acute toxicity point estimate

### **4-hydroxy-4-methylpentan-2-one :**

Acute oral toxicity : LD50: 3.002 mg/kg, rat

Acute inhalation toxicity : LC0: >= 7,6 mg/l, rat

Acute dermal toxicity : LD50: > 1.875 mg/kg, rat

---

## SECTION 12: Ecological information

### 12.1 Toxicity

Toxicity to fish :  
Remarks:  
No data is available on the product itself.

Toxicity to fish  
4-hydroxy-4-methylpentan-2-one : LC50: > 100 mg/l  
Exposure time: 96 h  
  
Species: *Oryzias latipes* (Orange-red killifish)

### 12.2 Persistence and degradability

Biodegradability : No data available

### 12.3 Bioaccumulative potential

Bioaccumulation : No data available

### 12.4 Mobility in soil

Mobility : No data available

### 12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## BASE COAT SPARKLING GLASS

Version 1.17

Revision Date 27.01.2016

Print Date 04.05.2016

### 12.6 Other adverse effects

Additional ecological information : The product contains dangerous substances for the environment (see chapter no 3). The concentration of each substance should be borne in mind in assessing the toxicological effects deriving from the preparation.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil. Disposal together with normal waste is not allowed. Special disposal required according to local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. The Waste code should be assigned in discussion between the user, the producer and the waste disposal company. The following Waste Codes are only suggestions: 150110\*

## SECTION 14: Transport information

### 14.1 UN number

ADR : UN 1263

IMDG : UN 1263

IATA : UN 1263

### 14.2 Proper shipping name

ADR PAINT

IMDG PAINT

IATA Paint

### 14.3 Transport hazard class(es)

ADR : 3

IMDG : 3

IATA : 3

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## BASE COAT SPARKLING GLASS

Version 1.17

Revision Date 27.01.2016

Print Date 04.05.2016

### 14.4 Packing group

#### ADR

Packing group : II

Classification Code : F1

Hazard Identification Number : 33

Labels : 3

#### IMDG

Packing group : II

Labels : 3

EmS Code : F-E,S-E

#### IATA

Packing group : II

Labels : 3

### 14.5 Environmental hazards

#### ADR

Environmentally hazardous : no

#### IMDG

Marine pollutant : no

#### IATA

Environmentally hazardous : no

### 14.6 Special precautions for user

not applicable

### 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Classified as Dangerous Goods according to NZS5433:1999 Transport of Goods on Land

## SECTION 15: Regulatory information

HSNO Classification: 3.1B, 6.3A, 8.3A, 6.9B

HSNO Group Standard HSR002662

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : not applicable

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## BASE COAT SPARKLING GLASS

Version 1.17

Revision Date 27.01.2016

Print Date 04.05.2016

REACH - List of substances  
subject to authorisation  
(Annex XIV) : not applicable

REACH - Restrictions on the  
manufacture, placing on the  
market and use of certain  
dangerous substances,  
preparations and articles  
(Annex XVII) : Banned and/or restricted

78-83-1	2-methylpropan-1-ol
108-94-1	cyclohexanone
64742-95-6	Low boiling point naphtha - unspecified
95-63-6	1,2,4-trimethylbenzene
108-67-8	1,3,5-trimethylbenzene
123-86-4	n-butyl acetate

MAL-Code-Number (DK) : 5-3 (1993)  
4.277-m<sup>3</sup> air/10 g

Risk classification according  
to VbF : Flash point less than 21 °C, at 15 °C not miscible in water  
Specially dangerous flammable liquids

Water contaminating class  
(Germany) : water endangering  
VWWWS A4

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006.  
Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and  
mixtures

### 15.2 Chemical Safety Assessment

No data is available on the product itself.

---

## SECTION 16: Other information

Full text of H-Statements referred to under sections 2 and 3.

# SAFETY DATA SHEET

according to Regulation (EC) No. 830/2015

## BASE COAT SPARKLING GLASS

Version 1.17

Revision Date 27.01.2016

Print Date 04.05.2016

---

EUH066	Repeated exposure may cause skin dryness or cracking.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Review date 11-7-2017

New Zealand HSNO and distributor information added

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.