### SAFETY DATA SHEET

Date of issue : 6 April 2019

Version : 2.11



### **Section 1. Identification**

Product code : T510/1L

Product name : T510 WB ENGINE BAY CONVERTER

Other means of

**:** 7510

identification Product type

: Liquid.

Recommended use and restrictions

Use of the substance/ : Co

mixture

: Coating.

**Uses advised against** : Not applicable.

Supplier's details : PPG INDUSTRIES NEW ZEALAND LTD

5 MONAHAN ROAD, MT WELLINGTON,

AUCKLAND www.ppgnz.co.nz

Telephone Numbers: 09 573 1620, 0800 659378 021 940 920 (24 Hours)

Emergency telephone number (with hours of

operation)

: New Zealand 0800 000 096 / Australia 1800 883 254 For international shipping emergencies: 1-412-391-1618

e-mail address of person responsible for this SDS

: ehsnz@ppg.com

### Section 2. Hazards identification

HSNO Classification : 6.3 - SKIN IRRITATION - Category B

6.4 - EYE IRRITATION - Category A (Irritant)

This material is classified as hazardous according to criteria in the Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001 and has been classified according to the Hazardous Substances (Classifications) Regulations 2001.

This material is not classified as DANGEROUS GOODS according to criteria in New Zealand Standard 5433:2012 Transport of Dangerous Goods on Land.

**GHS label elements** 

Signal word : Warning

**Hazard statements** : Causes mild skin irritation.

Causes serious eye irritation.

**Precautionary statements** 

**Prevention**: Wear eye or face protection. Wash thoroughly after handling.

Response : If skin irritation occurs: Get medical advice/attention. IF IN EYES: Rinse cautiously

with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. If eye irritation persists: Get medical advice/attention.

Storage : Not applicable.

Disposal : Not applicable.

New Zealand Page: 1/10

#### Product name T510 WB ENGINE BAY CONVERTER

### Section 2. Hazards identification

**Symbol** 



result in classification

Other hazards which do not : Prolonged or repeated contact may dry skin and cause irritation.

### Section 3. Composition/information on ingredients

Substance/mixture : Mixture **17510** Other means of

identification

**CAS** number/other identifiers

**Product code** : T510/1L

Hazardous ingredients	%	CAS number
<mark>3</mark> -butoxypropan-2-ol butan-1-ol		5131-66-8 71-36-3

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment or have an OEL and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

#### Description of necessary first aid measures

**Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids

apart for at least 10 minutes and seek immediate medical advice.

Inhalation : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is

irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by

trained personnel.

**Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and

water or use recognised skin cleanser. Do NOT use solvents or thinners.

: If swallowed, seek medical advice immediately and show the container or label. Keep Ingestion

person warm and at rest. Do NOT induce vomiting.

#### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

**Eye contact** : Causes serious eye irritation.

Inhalation : No known significant effects or critical hazards. : Causes mild skin irritation. Defatting to the skin. Skin contact Ingestion : No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

**Eyes** : Adverse symptoms may include the following:

pain or irritation watering

redness

Inhalation : No specific data.

> Page: 2/10 **New Zealand**

#### Product name T510 WB ENGINE BAY CONVERTER

### Section 4. First aid measures

Skin : Adverse symptoms may include the following:

> irritation redness dryness cracking

Ingestion : No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

**Specific treatments** : Not available.

Notes to physician : No specific treatment. Treat symptomatically. Contact poison treatment specialist

immediately if large quantities have been ingested or inhaled.

**Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It

may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

### Section 5. Firefighting measures

#### **Extinguishing media**

Suitable : Use an extinguishing agent suitable for the surrounding fire.

Not suitable : None known.

Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst.

**Hazardous thermal** decomposition products : Decomposition products may include the following materials:

Hazchem code

carbon oxides : Not available.

Special precautions for fire-

fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable

training.

**Special protective** equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).

**Environmental precautions** 

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

#### Methods and material for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

> **New Zealand** Page: 3/10

Product code T510/1L

Date of issue 6 April 2019

Version 2.11

#### Product name T510 WB ENGINE BAY CONVERTER

### Section 6. Accidental release measures

#### Large spill

Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

### Section 7. Handling and storage

# Precautions for safe handling

: Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

# Conditions for safe storage, including any incompatibilities

: Store between the following temperatures: 5 to 35°C (41 to 95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### Section 8. Exposure controls/personal protection

#### **Control parameters**

Ingredient name	ame Exposure limits	
<b>b</b> utan-1-ol	NZ HSWA 2015 (New Zealand, 11/2017). Absorbed through skin. WES-Ceiling: 150 mg/m³ WES-Ceiling: 50 ppm	

# Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

## Appropriate engineering controls

: No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

New Zealand Page: 4/10

#### Product name T510 WB ENGINE BAY CONVERTER

### Section 8. Exposure controls/personal protection

**Environmental exposure** controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Respiratory protection** 

: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

**Gloves** 

: For prolonged or repeated handling, use the following type of gloves:

May be used: nitrile rubber

Recommended: neoprene, butyl rubber

Eye protection

: Chemical splash goggles.

Skin protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

### Section 9. Physical and chemical properties

**Appearance** 

**Physical state** : Liquid. Colour : Colourless. **Odour** : Faint odour. **Odour threshold** : Not available. Hq Not available. **Melting point** : Not available. **Boiling point** : >37.78°C (>100°F)

Flash point : Closed cup: 100°C (212°F) [Product does not sustain combustion.]

**Material supports** 

combustion.

Flammability (solid, gas) : Not available. Lower and upper explosive

(flammable) limits

: Not available.

Page: 5/10 **New Zealand** 

#### Product name T510 WB ENGINE BAY CONVERTER

### Section 9. Physical and chemical properties

Vapour pressure : Not available.

Relative density : 1.02 Bulk Density (g/cm³) : 1.017

**Solubility** : Partially soluble in the following materials: cold water.

Partition coefficient: n-

octanol/water

: Not available.

Auto-ignition temperature : Not available.

Decomposition temperature : Not available.

Viscosity : Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)

**Viscosity** : 60 - 100 s (ISO 6mm)

### Section 10. Stability and reactivity

Stability: Stable under recommended storage and handling conditions (see Section 7).

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : No specific data.

**Incompatible materials** : Reactive or incompatible with the following materials:

oxidizing materials strong acids strong alkalis

**Hazardous decomposition** 

products

: Depending on conditions, decomposition products may include the following

materials: carbon oxides

Hazardous polymerisation : Under normal conditions of storage and use, hazardous polymerisation will not occur.

### **Section 11. Toxicological information**

#### Information on likely routes of exposure

Inhalation: No known significant effects or critical hazards.Ingestion: No known significant effects or critical hazards.Skin contact: Causes mild skin irritation. Defatting to the skin.

**Eye contact** : Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation: No specific data.Ingestion: No specific data.

**Skin contact**: Adverse symptoms may include the following:

irritation redness dryness cracking

**Eye contact** : Adverse symptoms may include the following:

pain or irritation watering

redness

Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Acute toxicity** 

New Zealand Page: 6/10

#### Product name T510 WB ENGINE BAY CONVERTER

### **Section 11. Toxicological information**

Product/ingredient name	Result	Species	Dose	Exposure
3-butoxypropan-2-ol	LD50 Dermal	Rabbit	3100 mg/kg	-
	LD50 Oral	Rat	2.2 g/kg	-
butan-1-ol	LC50 Inhalation Vapour	Rat	24000 mg/m <sup>3</sup>	4 hours
	LC50 Inhalation Vapour	Rat	8000 ppm	4 hours
	LD50 Dermal	Rabbit	3400 mg/kg	-
	LD50 Oral	Rat	790 mg/kg	-

**Conclusion/Summary** 

: There are no data available on the mixture itself.

**Irritation/Corrosion** 

**Conclusion/Summary** 

Skin: There are no data available on the mixture itself.Eyes: There are no data available on the mixture itself.Respiratory: There are no data available on the mixture itself.

**Sensitisation** 

**Conclusion/Summary** 

Skin : There are no data available on the mixture itself.Respiratory : There are no data available on the mixture itself.

Potential chronic health effects

General : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/

or dermatitis.

Carcinogenicity
 No known significant effects or critical hazards.
 Mutagenicity
 No known significant effects or critical hazards.
 Teratogenicity
 No known significant effects or critical hazards.
 Developmental effects
 No known significant effects or critical hazards.
 Fertility effects
 No known significant effects or critical hazards.

Chronic toxicity

Not available.

Carcinogenicity

**Conclusion/Summary**: There are no data available on the mixture itself.

**Mutagenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

**Teratogenicity** 

**Conclusion/Summary**: There are no data available on the mixture itself.

Reproductive toxicity

**Conclusion/Summary**: There are no data available on the mixture itself.

Not available.

**Aspiration hazard** 

Not available.

Numerical measures of toxicity

**Acute toxicity estimates** 

New Zealand Page: 7/10

#### Product name T510 WB ENGINE BAY CONVERTER

### **Section 11. Toxicological information**

Route	ATE value
	5706.9 mg/kg
Dermal	34084.8 mg/kg

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

### Section 12. Ecological information

**Ecotoxicity** 

: No known significant effects or critical hazards.

Aquatic and terrestrial toxicity

Not available.

#### Persistence/degradability

Not available.

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
3-butoxypropan-2-ol	1.15	-	low
butan-1-ol	0.88	-	low

#### **Mobility in soil**

Soil/water partition coefficient (K<sub>oc</sub>)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

Do not allow to enter drains or watercourses.

### Section 13. Disposal considerations

#### **Disposal methods**

The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may

New Zealand Page: 8/10

#### Product name T510 WB ENGINE BAY CONVERTER

### Section 13. Disposal considerations

retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Not suitable: : Do not allow to enter drains or watercourses.

The classification of the product may meet the criteria for a hazardous waste. Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL

PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

### 14. Transport information

	NZ	ADG	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-
Transport hazard class(es)	-	-	-	-
Packing group	-	-	-	-
Environmental hazards	No.	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.	Not applicable.

#### Additional information

NZ : None identified. : None identified. **ADG** Hazchem code : Not applicable. **IMDG** : None identified. **IATA** : None identified.

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

### Section 15. Regulatory information

**New Zealand Inventory of** Chemicals (NZIoC)

: All components are listed or exempted.

**HSNO Approval Number** 

: HSR002670 Subsidiary Hazard

**Emergency Management** 

: Level 1: Not applicable.

Regulations

Level 2: MSDS required when any amount is present in a workplace.

Level 3: Emergency Response Plans and Secondary Containment required when

10000L is stored.

: Not applicable. **Approved Handler** 

> **New Zealand** Page: 9/10

#### Product name T510 WB ENGINE BAY CONVERTER

#### Section 16. Other information

Date of issue : 6 April 2019

▼ Indicates information that has changed from previously issued version.

**Key to abbreviations** : STEL = Short Term Exposure Limit

TWA = Time-Weighted Average WES = Work Exposure Standard

References : Not available.

Organisation that prepared : EHS

the MSDS

#### **Disclaimer**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

New Zealand Page: 10/10